

ATTACHMENT II-1-14

PLAN FOR THE MANAGEMENT OF WASTE CODES F020-F023 AND F026-F027

1. PURPOSE AND SCOPE

In accordance with UAC R315-8-14.11, a management plan is required for the disposal of hazardous wastes with the listed codes F020, F021, F022, F023, F026, and F027. This attachment provides that plan.

2. WASTE CODES

The requirements of this Attachment apply to any waste characterized as F020, F021, F022, F023, F026, or F027. This plan applies in addition to any other requirements of this Permit and the regulations for other hazardous constituents present in the waste.

3. ACCEPTANCE CRITERIA

- a. Waste accepted for management and disposal in accordance with this plan shall be profiled, inspected, and sampled for waste acceptance in accordance with Attachment II-1, *Waste Analysis Plan*.
- b. Wastes subject to this Attachment shall not be placed in the Mixed Waste Landfill Cell prior to receipt of analytical confirmation that the waste meets the Land Disposal Restrictions. This restriction applies to the initial sampling as provided at condition V.6.e of Attachment II-1, *Waste Analysis Plan*. This provision also applies to annual or semi-annual confirmation sampling of ongoing waste streams, and to treatment verification sampling for waste that is treated at the Permittee's facility.

4. WASTE HANDLING AND STORAGE REQUIREMENTS

- a. Waste shall be managed in accordance with Module III, Storage and Treatment in Containers, Attachment III-1, *Container Management Plan*, and Module IV, *Storage and Treatment in Tanks*.
- b. Wastes subject to this Attachment shall be labeled "Dioxin/Furan Wastes – Special Management Requirements Apply".

5. TREATMENT AND DISPOSAL REQUIREMENTS

- a. All waste shall meet Land Disposal Restriction requirements unless a petition has been approved to allow disposal of restricted waste, or unless

a variance of the treatment standard has been granted by the Executive Secretary.

- b. Disposal shall be in accordance with Module V, Disposal in Landfills.
 - 1. Containerized wastes subject to this Attachment shall be disposed in CLSM lifts in a manner to minimize open-air exposure of the waste.
 - 2. Bulk wastes subject to this Attachment shall be covered by a minimum of 6 inches of clean fill within 24 hours of offloading the waste on the landfill cell. For purposes of this requirement, “clean fill” may be other wastes not subject to this plan.
- c. Wind dispersal shall be controlled in accordance with Attachment II-10, *Plan for Controlling Wind Dispersal*.
- d. Sumps containing wastes subject to this Attachment shall be subject to additional detection monitoring in accordance with condition VI.A.3.a of Module VI, *Groundwater Monitoring*.

END OF ATTACHMENT II-1-14